




The **COMPACT** System Boom Barrier is designed for ease of use and built to last. The boom arm is manufactured from rectangular Aluminium section and is raised and lowered by means of gas assisted strut for smooth operation. All steel parts are Hot Dip Galvanised and powder coated red for long service life, whilst the boom arm is white with red reflective strips for high visibility day or night, and includes an 'Anti-sit' feature along the top edge.

The **COMPACT** Boom Barrier has many applications including entrances and exits to car-parks, industrial/commercial estates, offices, public buildings etc.

Versions:

With fixed support post or integrated support arm.



The pivot post is surface fixed as standard (sub-surface fix is an option on request). The locking pin of the **COMPACT** Boom Barrier automatically engages with the boom arm in both open and closed positions, and is equipped as standard with a cylinder lock including 2 keys.

Additional locking options are:

Triangular key locking.

Keyed alike cylinder locks.

Customer supplied profile locks.

Dimensions:


Pivot Post: 220 x 100 x 100mm

Base plate: 295 x 295 x 10mm
(Drilled 6 holes 13mm Ø)


Support arm: 50 x 50 x 1,000mm H

Base plate: 200 x 200 x 10mm
(Drilled 4 holes 13mm Ø)

Alu-Boom Arm: 90 x 60mm



- Easily installed
- Unique gas-strut assisted operation
- Strong construction
- Lockable
- Compact design



COMPACT System Boom Barrier – with Gas-Strut			With integrated support arm			With fixed support post		
Description	Overall width (mm)	Max.drive through width (mm)	Delivery weight (kg/ea.)	Reference	Typical delivery time (working days)	Delivery weight (kg/ea.)	Reference	Typical delivery time (working days)
Surface fix with Cylinder lock and 2 keys	3,320	2,900	60	222.24.949	15 / 20 days	75	222.29.410	15 / 20 days
	3,820	3,400	70	222.25.156		85	222.28.372	
	4,320	3,900	80	222.22.549		95	222.25.184	
	4,820	4,400	90	222.27.060		105	222.23.852	
	5,320	4,900	100	222.22.516		115	222.27.798	
	5,820	5,400	110	222.26.548		125	222.20.858	
	6,320	5,900	120	222.24.380		135	222.29.758	

Accessories		Artikel	
Replacement triangular key		130.19.874	15 / 20 days
Pivot post for sub-surface fix (for use with pendulum support)		222.22.548	
Pivot and support post for sub-surface fix (for use with separate post)		222.26.318	
Triangular key operated lock		222.24.919	