



The **COMPACT** Counterweight Boom Barrier is designed for ease of use and built to last. All steel parts are Hot Dip Galvanised and powder coated red for long service life, whilst the aluminium boom arm is white with red reflective strips for high visibility day or night, and includes an 'Anti-sit' feature along the top edge.

The **COMPACT** Boom Barrier has many applications including entrances and exits to car-parks, industrial/commercial estates, offices, public buildings etc.

Versions:

With fixed support post or integrated support arm.

The pivot post is surface fixed as standard (sub-surface fix is an option on



request). The locking pin of the **COMPACT** Boom Barrier automatically engages with the boom arm in both open and closed positions, and is equipped as standard with a cylinder lock including 2 keys.

Additional locking options are:

Triangular key locking.

Keyed alike cylinder locks.

Customer supplied profile locks.

Dimensions:

Pivot Post: 220 x 100 x 100mm




Base plate: 295 x 295 x 10mm
(Drilled 6 holes 13mm Ø)

Support arm: 50 x 50 x 1,000mm H

Base plate: 200 x 200 x 10mm
(Drilled 4 holes 13mm Ø)

Alu-Boom Arm: 90 x 60mm

- Easily installed
- Smooth counterweight action
- Strong construction
- Lockable
- Clean modern design



		With integrated support arm				With fixed support post			
	Overall width (mm)	Max.drive through width (mm)	Delivery weight (kg/ea.)	Reference	Typical delivery time (working days)	Max.drive through width (mm)	Delivery weight (kg/ea.)	Reference	Typical delivery time (working days)
Surface fix with Cylinder lock and keys	3,000	1,895	75	226.24.283	15 / 20 days	—	—	—	15 / 20 days
	3,500	2,395	85	226.23.453		—	—	—	
	4,000	2,895	95	226.20.211		2,895	110	226.29.274	
	4,500	3,395	105	226.23.358		3,395	125	226.25.650	
	5,000	3,895	115	226.26.559		3,895	135	226.29.856	
	5,500	4,395	125	226.20.445		4,395	145	226.27.529	
	6,000	4,895	135	226.26.388		4,895	155	226.25.934	
	6,500	5,395	145	226.28.093		5,395	165	226.24.133	
	7,000	5,895	155	226.23.827		5,895	175	226.28.401	

Accessories			
Replacement triangular key		130.19.874	15 / 20 days
Pivot post for sub-surface fix (for use with pendulum support)			
Pivot and support post for sub-surface fix (for use with separate post)			
Triangular key operated lock			